

NOTES 1. HEAT TREAT 82.5 - 84.5 HR15N

2. NONE

| | | DIMENSIONS ARE IN INCHES TOLERANCES: | DRAWN | NAME | DATE | SEASTROM MFG | |
|-----|---|--|-----------|------|------|----------------------|--------------------|
| | | FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 | CHECKED | | | | |
| | | | ENG APPR. | | | PUSHON NUT | |
| | PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED. | THREE PLACE DECIMAL ±.005 | MFG APPR. | | | TUSHON NUT | |
| - 1 | | SPRING STEEL | Q.A. | | | | |
| - 1 | | | COMMENTS: | | | | |
| | | SEE NOTE 2 | | | | SIZE DWG. NO. 2713-4 | REV. |
| - 1 | | DRAWING IS NOT TO SCALE | | | | 11 Z/ 10 T |) -)F 1 |