



NOTES

- 1. BERYLLIUM COPPER, ANNEALED
- 2. HEAT TREAT: 73-79 HR15N
- 3. TIN PER ASTM B545 CLASS B
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES:		NAME	DATE	SEASTROM MFG		
		DRAWN				31/13/1/0/1/1/1/1	
	FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg	CHECKED					
	TWO PLACE DECIMAL ±.01	ENG APPR.			SPRING CLIP		
	THREE PLACE DECIMAL ±.005	MFG APPR.				31 KING CLII	
:	SEE NOTE 1	Q.A.					
		COMMENTS:					
	HEAT TREAT						
	SEE NOTE 2				A DW	4505-18X35-21-1-T	REV.
	FINISH						-
	SEE NOTE 3	DRAWING IS NOT TO SCALE				ISHEET 1 C)F 1