



NOTES
1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. TIN PER ASTM B545 CLASS B

4. DIMENSIONS ARE TAKEN WITH THE PART
CLAMPED TO A FLAT SURFACE AND A DUMMY
COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	SEASTROM MFG	
		DRAWN			
		CHECKED		SPRING CLIP	
		ENG APPR.			
		MFG APPR.			
MATERIAL SEE NOTE 1	Q.A.			DRAWING IS NOT TO SCALE	
HEAT TREAT SEE NOTE 2	COMMENTS:				
FINISH SEE NOTE 3	SIZE A	DWG. NO.	4511-37-75-1-T	REV. -	SHEET 1 OF 1