

- 1. SPRING STEEL, ANNEALED
- 2. QUENCH & TEMPER 80-83 HR15N
- 3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2 w/BAKE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01		NAME	DATE		SEASTROM MFG	
		DRAWN					
		CHECKED					
		ENG APPR.			SPRING CLIP		
	THREE PLACE DECIMAL ±.005	MFG APPR.					
E	SEE NOTE 1	Q.A.					
		COMMENTS:					
	HEAT TREAT						
	SEE NOTE 2						REV.
	FINISH				A 4513-23-37-2-C2 -		
	SEE NOTE 3	DRAWING IS NOT TO SCALE				SHEET 1 O	F 1