

- 1. SPRING STEEL, ANNEALED
- 2. QUENCH & TEMPER 80-83 HR15N
- 3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2 w/BAKE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES		NAME	DATE		SEASTROM MFG		
	TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN				3LASINOM MI G		
		CHECKED						
		ENG APPR.			SPRING CLIP			
	THREE PLACE DECIMAL ±.005	MFG APPR.				31 KING CLII		
	SEE NOTE 1	Q.A.						
		COMMENTS:						
	HEAT TREAT							
	SEE NOTE 2					DWG. NO.	REV.	
	FINISH SEE NOTE 3				Α	4513-40-37-2-C2	-	
		DRAWING IS NOT TO SCALE				SHEET 1 C)F 1	