

- 2. QUENCH & TEMPER: 80-83 HR15N
- 3. NONE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005		NAME	DATE		SEASTROM MFG		
		DRAWN			3LASTROM MIG			
		CHECKED			SPRING CLIP			
		ENG APPR.						
		MFG APPR.						
	MATERIAL	Q.A.						
	SEE NOTE 1	COMMENTS:			1			
	HEAT TREAT							
	SEE NOTE 2				A D	DWG. NO.	٠.	
	SEE NOTE 3					4519-28X35-37-2 -		
		DRAWING IS NOT TO SCALE				SHEET 1 OF 1	Ī	