



### **No. HOLES: 1**

#### NOTES

1. SPRING STEEL, ANNEALED

2. QUENCH & TEMPER: 80-83 HR15N

3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2 w/BAKE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

#### **PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL ± 1/32  
ANGULAR: MACH ± 1/2 Deg  
TWO PLACE DECIMAL ± .01  
THREE PLACE DECIMAL ± .005

MATERIAL  
SEE NOTE 1

HEAT TREAT  
SEE NOTE 2

FINISH  
SEE NOTE 3

NAME	DATE
DRAWN	
CHECKED	
ENG APPR.	
MFG APPR.	
Q.A.	
COMMENTS:	
DRAWING IS NOT TO SCALE	

**SEASTROM MFG**

**SPRING CLIP**

SIZE	DWG. NO.	REV.
<b>A</b>	<b>4519-84X140-25-2-C</b>	<b>-</b>
		SHEET 1 OF 1