



#### NOTES

1. SPRING STEEL, ANNEALED

2. QUENCH & TEMPER 80-83 HR15N

3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2 w/BAKE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

#### PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL  $\pm 1/32$   
ANGULAR: MACH  $\pm 1/2$  Deg  
TWO PLACE DECIMAL  $\pm .01$   
THREE PLACE DECIMAL  $\pm .005$

MATERIAL  
SEE NOTE 1

HEAT TREAT  
SEE NOTE 2

FINISH  
SEE NOTE 3

|                         |      |      |              |                 |      |
|-------------------------|------|------|--------------|-----------------|------|
|                         | NAME | DATE | SEASTROM MFG |                 |      |
| DRAWN                   |      |      |              |                 |      |
| CHECKED                 |      |      |              |                 |      |
| ENG APPR.               |      |      |              |                 |      |
| MFG APPR.               |      |      |              |                 |      |
| Q.A.                    |      |      | SPRING CLIP  |                 |      |
| COMMENTS:               |      |      |              |                 |      |
| DRAWING IS NOT TO SCALE |      |      | SIZE         | DWG. NO.        | REV. |
|                         |      |      | A            | 4527-26-50-2-C2 | -    |
|                         |      |      | SHEET 1 OF 1 |                 |      |