



No. HOLES: 1

NOTES

1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. SILVER PLATE PER ASTM B700 TYPE 1 GRADE A CLASS S, $2.5\mu\text{m}$ TH
w/NICKEL UNDERPLATE

4. DIMENSIONS ARE TAKEN WITH THE PART
CLAMPED TO A FLAT SURFACE AND A DUMMY
COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL $\pm 1/32$
ANGULAR: MACH $\pm 1/2$ Deg
TWO PLACE DECIMAL $\pm .01$
THREE PLACE DECIMAL $\pm .005$

MATERIAL
SEE NOTE 1

HEAT TREAT
SEE NOTE 2

FINISH
SEE NOTE 3

NAME	DATE
DRAWN	
CHECKED	
ENG APPR.	
MFG APPR.	
Q.A.	
COMMENTS:	
DRAWING IS NOT TO SCALE	

SEASTROM MFG

SPRING CLIP

SIZE	DWG. NO.	REV.
A	4547-62-43-1-S	-

SHEET 1 OF 1