


NOMINAL BRAID WIDTH	NOMINAL BRAID THICKNESS	NOMINAL CIRC MILS	CAPACITY AMPS	APPROX AWG EQUIV
.500	.030	9,600	53	10



MATERIALS
 GROUND ENDS: COPPER (TIN SOLDER DIP)
 BRAID: TINNED COPPER
 INSULATION: HEAT SHRINKABLE TUBING

ASSEMBLY
 TERMINALS (GROUND ENDS) ARE
 CRIMPED AND SOFT TIN SOLDERED TO
 BRAID.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 SEASTROM MANUFACTURING. ANY
 REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT THE WRITTEN PERMISSION OF
 SEASTROM MANUFACTURING IS
 PROHIBITED.

DIMENSIONS ARE IN INCHES ALL DIMENSIONS ARE FOR REFERENCE ONLY		NAME	DATE	SEASTROM MFG
MATERIAL SEE NOTES		DRAWN		
FINISH SEE NOTES		CHECKED		SIZE A DWG. NO. 5025-104-18.000 REV. -
DRAWING IS NOT TO SCALE		ENG APPR.		
		MFG APPR.		
		Q.A.		
		COMMENTS:		