


NOMINAL BRAID WIDTH	NOMINAL BRAID THICKNESS	NOMINAL CIRC MILS	CAPACITY AMPS	APPROX AWG EQUIV
1.000	.045	20,800	85	7



MATERIALS
GROUND ENDS: COPPER (TIN SOLDER DIP)
BRAID: TINNED COPPER
INSULATION: HEAT SHRINKABLE TUBING

ASSEMBLY
TERMINALS (GROUND ENDS) ARE
CRIMPED AND SOFT TIN SOLDERED TO
BRAID.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

DIMENSIONS ARE IN INCHES ALL DIMENSIONS ARE FOR REFERENCE ONLY		NAME	DATE	SEASTROM MFG	
	DRAWN				
	CHECKED			GROUND STRAP	
	ENG APPR.				
	MFG APPR.				
MATERIAL SEE NOTES	Q.A.			SIZE DWG. NO. REV. A 5025-105-2.000 -	
FINISH SEE NOTES	COMMENTS:				
DRAWING IS NOT TO SCALE				SHEET 1 OF 1	