

NOTES 1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE: 6

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

	DIMENSIONS ARE IN INCHES		NAME	DATE	SEASTROM MFG
	TOLERANCES:	DRAWN			
	FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	CHECKED			SOLDER LUG
		ENG APPR.			
		MFG APPR.			
	BRASS, HALF HARD	Q.A.			
		COMMENTS:			
	SEE NOTE 1				SIZE DWG. NO.
	DRAWING IS NOT TO SCALE				A 5413-3-TL2 -
					I SHFFT 1 OF 1