

NOTES
1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE: 5/16

3. DIMENSIONS APPLY PRIOR TO PLATING.

I KOI KILIAKI AND CONIIDLINIIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg		NAME	DATE	SEASTROM MFG
		DRAWN			3LASTROM MI O
		CHECKED			
	TWO PLACE DECIMAL ±.01	ENG APPR.			SOLDER LUG
	THREE PLACE DECIMAL ±.005	MFG APPR.			3OLDLK LUG
	MATERIAL	Q.A.			
	BRASS, HALF HARD	COMMENTS:			
	SEE NOTE 1				SIZE DWG. NO.
	DRAWING IS NOT TO SCALE				A 5413-9-TL2 -
	DIVAMING IS NOT TO SCALE				I SHEET 1 OF 1