

NOTES

1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. WIRE SIZE: 14-20

3. SCREW SIZE: 2

4. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE	SEASTROM MFG		
	CHECKED					
	ENG APPR.			SOLDER LUG		
	MFG APPR.					
MATERIAL	Q.A.]		
BRASS	COMMENTS:			1		
FINISH SEE NOTE 1					DWG. NO.	REV.
DRAWING IS NOT TO SCALE				A	5450-12B-TL2	
				1	SHEET 1	I