

NOTES:

1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. DIMENSIONS APPLY BEFORE PLATING

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN	NAME	DATE	SEASTROM MFG		
		CHECKED					
		ENG APPR.				EXPANSION PLUG	
	THREE PLACE DECIMAL ±.005	MFG APPR.			DOME		
DLE	MATERIAL COLD ROLLED STEEL	Q.A.					
		COMMENTS:					
	FINISH SEE NOTE 1					DWG. NO.	REV.
	DRAWING IS NOT TO SCALE				Α	5790-9-TL2	-
						SHEET 1	OF 1