

NOTES 1. PASSIVATE PER AMS2700 METHOD 1 TYPE 2 CLASS 1

2. HEAT TREAT: TH1050 CONDITION (38-44 HRC)

3. NUMBER OF WAVES: 3

4. DIMENSIONS APPLY BEFORE PLATING

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE	SEASTROM MFG			
	CHECKED			WAVE SPRING WASHER			
	ENG APPR.						
	MFG APPR.						
17-7PH STAINLESS STEEL	Q.A.						
	COMMENTS:						
SEE NOTE 1				SIZE	DWG. NO.		RFV.
SEE NOTE I	-			Α			_
DRAWING IS NOT TO SCALE						SHEET 1 C	DF 1