REFEERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 $.010 \pm .0010$.875 ± .015 .955 MAX $.500 \pm .020$.645 MAX $.625 \pm .010$ $1.000 \pm .010$ - $.113 \pm .003 .375 \pm .005$ -.125 ± .005 **NOTES**

- 1. BERYLLIUM COPPER, ANNEALED
- 2. HEAT TREAT: 73-79 HR15N
- 3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01		NAME	DATE		SEASTROM MFG	
		DRAWN					
		CHECKED					
		ENG APPR.				SPRING CLIP	
	THREE PLACE DECIMAL ±.005	MFG APPR.					
	SEE NOTE 1	Q.A.					
		COMMENTS:					
	SEE NOTE 2				SIZE	^{DWG. NO.} 4514-87-100-1-C2	REV.
	FINISH				Α		-
	SEE NOTE 3	DRAWING IS NOT TO SCALE				ISHEET 1 C)F 1