## REFEERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 $.010 \pm .0020$ .875 ± .015 .955 MAX $.500 \pm .020$ .645 MAX $.625 \pm .010$ $1.000 \pm .010$ - $.113 \pm .003 .375 \pm .005$ -.125 ± .005 NOTES

- 1. SPRING STEEL, ANNEALED
- 2. QUENCH & TEMPER 80-83 HR15N
- 3. NONE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01		NAME	DATE		SEASTROM MFG	
		DRAWN					
		CHECKED					
		ENG APPR.			SPRING CLIP		
	THREE PLACE DECIMAL ±.005	MFG APPR.			3FRING CLIF		
E	SEE NOTE 1	Q.A.					
		COMMENTS:			1		
	HEAT TREAT					<u>,                                      </u>	
	SEE NOTE 2				SIZE	<sup>DWG. NO.</sup> 4514-87-100-2	٧.
	FINISH						
	SEE NOTE 3	DRAWING IS NOT TO SCALE				SHEET 1 OF	1