



- NOTES
1. BERYLLIUM COPPER, ANNEALED
  2. HEAT TREAT: 73-79 HR15N
  3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2
  4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
  5. DIMENSIONS APPLY PRIOR TO PLATING.

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005	
MATERIAL SEE NOTE 1	
HEAT TREAT SEE NOTE 2	
FINISH SEE NOTE 3	

	NAME	DATE
DRAWN		
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		
DRAWING IS NOT TO SCALE		

<b>SEASTROM MFG</b>	
<b>SPRING CLIP</b>	
SIZE <b>A</b>	DWG. NO. <b>4521-100-100-1-C2-</b>
REV. SHEET 1 OF 1	