REFEERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 .016 ± .0013 .950 MAX .950 ± .015 $.515 \pm .020$ - .640 MAX → 1.500 ± .010 - $.250 \pm .005$ $.073 \pm .003$ 1.000 ± .005 $.400 \pm .010$

NOTES

1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. NONE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

- 1	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE		SEASTROM MFG		
		CHECKED				SPRING CLIP		
		ENG APPR.						
		MFG APPR.						
	see note 1	Q.A.						
		COMMENTS:						
	SEE NOTE 2				SIZE	^{DWG. NO.} 4555-95-150-1	REV.	
	FINISH SEE NOTE 3				A 4555-95-150-1	4555-95-150-1	-	
		DRAWING IS NOT TO SCALE				SHEET 1 (OF 1	