REFEERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 $.016 \pm .0020$.950 MAX $.950 \pm .015$ $.515 \pm .020$ - .640 MAX → 1.500 ± .010 -- $.250 \pm .005$ $.073 \pm .003$ 1.000 ± .005

NOTES

- 1. SPRING STEEL, ANNEALED
- 2. QUENCH & TEMPER 80-83 HR15N
- 3. NICKEL PLATE PER AMS QQ-N-290 CLASS 1 GRADE G w/BAKE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

 $.400 \pm .010$

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN	NAME	DATE		SEASTROM MFG	
		CHECKED				SPRING CLIP	
		ENG APPR.					
	THREE PLACE DECIMAL ±.005	MFG APPR.					
	see note 1	Q.A.					
		COMMENTS:					
	SEE NOTE 2				SIZE	DWC NO	RFV.
	FINISH				A	4555-95-150-2-N	_
	SEE NOTE 3	DRAWING IS NOT TO SCALE				SHEET 1 O	F 1