

- 2. HEAT TREAT: 73-79 HR15N
- 3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01		NAME	DATE		SEASTROM MFG	
		DRAWN			3LASTROM MIG		
		CHECKED			SPRING CLIP		
		ENG APPR.					
	THREE PLACE DECIMAL ±.005	MFG APPR.			3FRING CLIF		
	SEE NOTE 1	Q.A.					
		COMMENTS:			1		
	HEAT TREAT					,	
	SEE NOTE 2				SIZE	DWG. NO. AF / 7 07 7F 1 CO REV.	
	SEE NOTE 3					4567-37-75-1-C2 -	
		DRAWING IS NOT TO SCALE				SHEET 1 OF 1	