## REFERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 .256 ± .010 - $.500 \pm .010$ .187 ± .010 .406 ± .010 .128 ± .010 -R.060 ± .010 $.040 \pm .0040$ - .375 ± .010 2.131 REF. ——\\_ **NOTES**

1. TIN-LEAD PER AMS-P-81728 w/COPPER UNDERPLATE. MUST CERT SOLDERABILITY TO MIL-STD-202, M208

2. DIMENSIONS APPLY PRIOR TO PLATING.

3. # OF TERMINALS: 6

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN	NAME	DATE	SEASTROM MFG
		CHECKED			TEDAAINIA I CTDID
		ENG APPR.			
	THREE PLACE DECIMAL ±.005	MFG APPR.		SEASTRO	_
	MATERIAL	Q.A.			GROUNDING
	BRASS	COMMENTS:			
E	SEE NOTE 1				
	DRAWING IS NOT TO SCALE				A   JUUO-0-ILI   -