## REFERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 2X Ø.156 ± .003 4X Ø.050 ± .003 .615 ± .005 $1.300 \pm .010$ $.960 \pm .005$ $.281 \pm .005$ .281 ± .005 $.003 \pm .0003$ .810 ± .010

## NOTES 1. CASE STYLE:

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

DIMENSIONS ARE IN INCHES		NAME	DATE	SEASTROM MFG
TOLERANCES:	DRAWN			3LASTROWT WILL
FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg	CHECKED			
TWO PLACE DECIMAL ±.01	ENG APPR.			SOLIDSTATE INSULATE
THREE PLACE DECIMAL ±.005	MFG APPR.			30LIDSTATE INSULATE
MATERIAL	Q.A.			
KAPTON	COMMENTS	:		
FINISH				CITE LOUIS NO
NONE				SIZE DWG. NO. 5216-1
DRAWING IS NOT TO SCALE				SHEFT 1.C