REFEERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 $.500 \pm .010$ $.040 \pm .004$ $1.105 \pm .010$ $\emptyset.150 \pm .005$.223 ± .016 - $.344 \pm .016$ **NOTES** 1. BRIGHT TIN PLATE PER ASTM B545, CLASS B NAME DATE 2. SCREW SIZE: 6 DIMENSIONS ARE IN INCHES SEASTROM MFG TOLERANCES: DRAWN FRACTIONAL±1/32 CHECKED ANGULAR: MACH±1/2 Deg 3. DIMENSIONS APPLY PRIOR TO PLATING. ENG APPR. TWO PLACE DECIMAL ±.01 **SOLDER LUG** THREE PLACE DECIMAL ±.005 PROPRIETARY AND CONFIDENTIAL MFG APPR. THE INFORMATION CONTAINED IN THIS MATERIAL Q.A. DRAWING IS THE SOLE PROPERTY OF BRASS, HALF HARD COMMENTS: SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE SIZE DWG. NO. 54.

SEE NOTE 1

DRAWING IS NOT TO SCALE

REV.

SHEET 1 OF 1

5454-9B

WITHOUT THE WRITTEN PERMISSION OF

SEASTROM MANUFACTURING IS

PROHIBITED.