REFERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 15° ± 4° .308 ± .016 1.224 ± .020 $\emptyset.900 \pm .005$.564 ± .010 Ø.197 ± .005 $.063 \pm .0035$ 1.236 ± .010 NOTES:

1. NONE

PROPRIETARY AND CONFIDENTIAL	THREE PLACE DEC
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	MATERIAL ALUMINUM
SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	FINISH SEE NOTE 1
SEASTROM MANUFACTURING IS PROHIBITED.	DRAWING IS N

	DIMENSIONS ARE IN INCHES TOLERANCES:		NAME	DATE]			
		DRAWN				SEASTROM MFG		
FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg	CHECKED							
	TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	ENG APPR.			1	DETAINING WASHED		
		MFG APPR.]	retaining washer		
	MATERIAL	Q.A.			1			
	ALUMINUM	COMMENTS:		1				
SEE NOTE 1 DRAWING IS NOT TO SCALE				SIZE	SIZE DWG, NO. REV.			
				A	5759-26	_		
					H	CUEET 1 C	L 1	