



SECTION A-A

NOTES

1. SCREW SIZE: 5/16
2. CASE HARDENED (550+100) HV10
3. PARTS SHOULD BE FREE FROM BURRS AND VISUAL DEFECTS.
4. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

| | | | | | |
|--|-----------|------|-------------------------|------------|------|
| DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005 | NAME | DATE | SEASTROM MFG | | |
| | DRAWN | | | | |
| | CHECKED | | CONCAVE WASHER | | |
| | ENG APPR. | | | | |
| | MFG APPR. | | | | |
| MATERIAL | COMMENTS: | | SIZE | DWG. NO. | REV. |
| COLD ROLLED STEEL | | | A | 5785-7-312 | - |
| HEAT TREAT | | | DRAWING IS NOT TO SCALE | | |
| SEE NOTE 2 | | | SHEET 1 OF 1 | | |
| FINISH | | | | | |
| NONE | | | | | |