REFERENCE SEASTROM WORKMANSHIP STD. 8.4.1.W2 .188 .198 Ø.753 MAX Ø1.264 Ø.765 MIN .234-

NOTES 1. NONE

2. SCREW SIZE: 3/4

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS

DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	I DIMENSIONS ARE IN INCHES			
	TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN		
		CHECKED		
		ENG APPR.		
	THREE PLACE DECIMAL ±.005	MFG APPR.		
	MATERIAL HIGH CARBON SPRING STEEL	Q.A.		
	THOTI CARBOTT OF KITTO STEEL	COMMENTS	i.	
	FINISH SEE NOTE 1			
	DRAWING IS NOT TO SCALE			

	NAME	DATE			450	~	
DRAWN				SEASTROM <i>N</i>	VIFG		
CHECKED							
ENG APPR.			SPRING LOCKWASHER				
MFG APPR.			31 KING LOCKWASITEK				
Q.A.							
COMMENTS:							
				DWG. NO.		REV.	
			Α	5850-26		-	
					SHEET 1 C	OF 1	